

# TRI-FIXX

- **Hex head, 14 gauge x 65mm**
- **Class 3 corrosion resistance in accordance with AS3566.2-2002**
- **Assembled with a 32mm waterproof, durable & UV resistant Seal**
- **Specially designed wings for drilling 10mm clearance hole in fibreglass roof sheeting. Only one tool required**
- **Capable of self drilling steel up to 5.0mm thick**



# SKYFIXX™

## For Industrial Fibreglass Roofing

**NO PRE-DRILLING OF CLEARANCE HOLE REQUIRED**

**ONE STEP EASY APPLICATION FOR FIXING INDUSTRIAL  
FIBREGLASS ROOF SHEETING TO STEEL  
SAVES TIME AND MONEY**

Distributed by:

TRI-FIXX PTY. LTD.  
26-30 Howleys Road  
Notting Hill, Victoria 3168  
Telephone: (61) 03 9543 8422  
Facsimile: (61) 03 9543 4431  
Email: [sales@trifixx.com.au](mailto:sales@trifixx.com.au)

TRI-FIXX (NSW) PTY. LTD.  
28 East Street  
Granville, NSW 2142  
Telephone: (61) 02 9682 7644  
Facsimile: (61) 02 9637 2440  
Email: [sales@trifixxnsw.com.au](mailto:sales@trifixxnsw.com.au)